

The TALL Group of Companies

Authorised Distributor and Service Partner to



Passbook Printer Range

PR9

SPECIALISED PRINTER

As the most competitive product on the market today, **PR9** specialised printer is designed to be the **most advanced solution for banking transaction and financial services.**

PR9 offers users the **lowest cost of ownership.** The long lasting, heavy duty print head with life of more than 400 million dots per needle assures consistent and outstanding performance.



Passbook Printer Range

PR9

DESCRIPTION

PR9 handles a **wide type of formats and thickness**: single sheet up to A4 size, passbooks, vouchers, tickets, multi-copy forms, etc. Its superior document handling (auto alignment and auto document thickness adoption) capability ensures a **quick and efficient processing** on the documents inserted with variable thickness at different angles in any position.

PR9 fits into your existing IT environment thanks to a comprehensive range of industry standard and financial emulations. It offers a **wide variety of optional devices**, such as scanner, RFID, HMSR and MICR, which greatly contribute to expand its functionality and range of applications.

MAIN CHARACTERISTICS



SUPERIOR DOCUMENT HANDLING CAPABILITIES



LOW COST OF OWNERSHIP



EASY INTEGRATION



TECHNICAL SPECIFICATIONS

GENERAL CHARACTERISTICS

Technology	24 pin dot matrix (550 Million dots/needle life)
Resolution	240 x 360 dpi
Fonts	HSD, Draft, Roman, Sans Serif, Italic OCR-A, OCR-B, E13B
Pitch	10, 12, 13.8, 15, 16.6, 17.1, 18, 20, 30 cpi
Printing Speed at 10cpi	VHSD: 570 cps - HSD: 510 cps Draft: 400 cps NLQ: 200 cps - LQ: 150 cps
Line Length	38.8mm (94 columns at 10 cpi)
Line Spacing	1/5", 1/6", 1/8", n/72", n/180", n/216", n/240", n/360"
Copies	original + 6 copies
Emulation	IBM PP 11 & X24, PR2/PR40+, OKI 5530SC LQ 1600K, IBM 9068, IBM 4722, Hitachi
Document Handling	* Feed Width: 245mm * Completely flat paper bed * Automatic insertion with auto-border * Automatic document-thickness adaption
Ribbon Cartridge	Standard: 5 million Optional: 10 million characters

Interface

Standard: Serial RS-232

Optional: IEEE 1284 Parallel, USB2.0 LAN,
and 2nd Serial RS-232

Noise Level

<54 dBA (ISO7779)

Power Consumption

Min 5.7W

Voltage

220V/50Hz or 110V/60Hz

Certifications

CE

Dimensions (wxDxH)

398 x 296 x 201mm (15.67" x 11.65" x 7.91")

Weight

9 kg

OPTIONS

MICR

Recognized fonts: CMC7, E13B

Speed: >30 cps (CMC7) or >18 cps (E13B)

HMSR

DIN/ISO, ANSI and IBM3604, IBM 4746,

ISO7811, HT-2751-C1Z, ISO8484

RFID

Frequency: 13.56 MHz

Standards: ISO 14443 A/B, ISO15693

SCANNER

A4 single/double sided,

RGB 24 bit/256 greys/16 greys/BW;

600/300/200 dpi

PLEASE NOTE: Product performances are referred to as an appropriate use under optimal conditions. We reserve the right to change technical specifications. The registered trademarks are the property of their respective owners.

TALL Security Print Limited
Unit 2, Pembroke Court
Manor Park
Runcorn, Cheshire WA7 1TJ
Tel: 01928 579200

CHECKPRINT Limited
Alan Bray Close
Dodwells Bridge Industrial Estate
Leicestershire LE10 3BP
Tel: 01455 615616

DLRT Limited
Lissue Industrial Estate East
Unit 3, 9 Lissue Walk
Lisburn, Co. Antrim BT28 2LU
Tel: 028 9262 2999